

CNA-4

It counts the number of tightened bolts which prevents missed tightening.



Specifications

COUNT DISPLAY	2 digits, 7 segments, LED
CONFORMITY DISPLAY	20 X 30 mm lamp display
COUNT INPUT	Relay contacts (OK and NG) ; 24V, 1A resistive load
PRESET MAX. VALUE	99 counts (by DIP switches)
SELECT FUNCTION	Max. 4 group settings (2 group settings as optional mode.)
JUDGMENT	OK: Count input has reached the preset number. NG: The count input has exceeded the preset value. The count input has not reached the preset number.
CONFORMITY OUTPUT	OK: Green lamp lights. NG: Red lamp lights, buzzer sounds OK and NG respectively relay contacts (24V, 1A resistance load)
OPERATING TEMPERATURE [°C]	0 to 40
POWER SOURCE AC[V]	100 50/60Hz within 15W 90-110VAC, 50/60Hz within 15W
DIMENSION [mm]	150 X 210 X 50 (W, D, H)
WEIGHT APPROX. [kg]	1.3

NOTE

1. Auto judgment timer, auto reset timer, and double count prevention timer functions are available by changing inside dip switches.
2. CNA-4 can not receive two signals simultaneously from the different unit.
3. Standard or optional mode can be changed with internal dip switches.
4. Power source AC220V is optional.



[Print](#)



[Close](#)

©2004 Tohnichi America Corp. All Rights Reserved.