


DOT



**Suitable for torque wrench calibration.**



**Select proper model according to unit of measure as following color code :**

S.I. =      Metric =      American =     

Accuracy  $\pm 2\%$ 

Model			Torque Range						Inlet Drive	Torque Wrench Max. Effective Length	Dimension			Weight Approx.	Accessory		
S.I.	Metric	American	Min.-Max.			Graduation					Overall length	Overall Width	Overall Height		Socket (Female)		Hex Adapter (Male)
			S.I.	Metric	American	S.I.	Metric	American							mm	in.	
DOT 35N	350 DOT	DOT300I	N.m 5-35	kgf.cm 50-350	in.lbs 40-300	N.m 0.1	kgf.cm 1	in.lbs 1	9.53 mm	400 mm 15 3/4 in	487 mm 19 5/32 in	257 mm 10 1/8 in	222 mm 7 19/32 in	8 kg	6.35	1/4	10, 13, 19, 12, 14, 17
DOT 50N	500 DOT	DOT430I	5-50	50-500	40-430	0.2	2	2	3/8 in					17 21/32 lbs.			
DOT 100N	1000 DOT	DOT1000I	10-100	100-1000	90-1000	0.5	5	5	12.7 mm 1/2 in					6.35, 9.53	1/4 & 3/8		
DOT 300N	3000 DOT	DOT200F	30-300	300-3000	ft.lbs 20-200	1	10	ft.lbs 1	19.05 mm	660 mm 26 in	765 mm 30 1/8 in	317 mm 12 1/2 in	270 mm 8 11/16 in	10 kg 22 1/16 lbs.	12.7	1/2	17, 22, 27, 19, 24, 30
DOT 700N	7000 DOT	DOT500F	70-700	700-7000	50-500	2	20	2	3/4 in	1260 mm 49 19/32 in	1365 mm 53 3/4 in	388 mm 15 9/32 in	272 mm 9 9/16 in	25 kg 55 1/8 lbs.	-	-	22, 27, 29, 30, 32, 36

**NOTE**

1. Measurement for clockwise direction only.
  2. Special specifications, such as counterclockwise measurement, without loading device, etc., are supplied upon request.
- 



[Print](#)



[Close](#)

©2004 Tohnichi America Corp. All Rights Reserved.