


ST



Revolutionary compact, high accuracy and easy to operate, Suitable for nutrunner torque check.



Select proper model according to unit of measure as following color code :

S.I. = Metric = American =

Accuracy F.S. $\pm 1\%$ + 1digit

Model			Torque Range						Square Drive		Dimension				Weight Approx.	
S.I.	Metric	American	Min.-Max.			Graduation			mm	in	Overall Length		Max. Diameter		kg	lbs.
			S.I.	Metric	American	S.I.	Metric	American			mm	in	mm	in		
ST12N	ST120	ST100I-3A	N.m	kgf.cm	in.lbs	N.m	kgf.cm	in.lbs	9.5	3/8	75	2 61/64	48	1 29/32	0.25	9/16
ST24N	ST240	ST200I-3A	1.2-12	12-120	10-100	0.05	0.5	0.5								
ST48N	ST480	ST400I-4A	2.4-24	24-240	20-200	0.1	1	1								
ST120N	ST1200	ST1000I-4A	4.8-48	48-480	40-400	0.2	2	2	12.7	1/2	135	5 5/16	66.5	2 5/8	1.3	2 7/8
ST240N	ST2400	ST85F-4A	12-120	120-1200	100-1000	0.5	5	5								
ST480N	ST4800	ST340F-6A	24-240	kgf.m	ft.lbs	1	kgf.m	ft.lbs	19.0	3/4	135	5 5/16	66.5	2 5/8	1.3	2 7/8
ST1200N	ST12000	ST850F-8A	48-480	4.8-48	34-340	2	0.2	2								
			120-1200	12-120	85-850	3	0.3	5	25.4	1						

Common Specification

DATA MEMORY	100 data
ARITHMETIC FUNCTION	Maximum, Minimum, Means
MEASUREMENT MODE	PEAK/RUN
ZERO ADJUSTMENT	C key, Auto zero
DATA OUTPUT	Infrared output
RESET	Auto reset (Changeable by each 0.5 sec.)
POWER	Ni-Cd Battery
CONTINUOUS OPERATION [h]	2
BATTERY CHARGE [h]	3
OPERATING CONDITION [°C]	Temperature 0 ~ 40

NOTE

1. Do not use ST for impact wrench and impulse wrench.
 2. For data transfer, use DATA TANK (R-DT100-3).
 3. Protector cover is attached to ST480N and ST1200N.
 4. AC adapter is included for recharging the unit.
-

[Print](#)[Close](#)

©2004 Tohnichi America Corp. All Rights Reserved.