

TP/TTF/DTF+ATF

Attachments for TCF to achieve precise torque measurement.



| Model | Torque Range | | | Adapting Model | Inlet | | Dimension in | | | | Weight Approx. | |
|---------|-----------------|------------------|------------------|-----------------------|---------------|-------------|--------------|--------|--------|----------|----------------|--------|
| | Min. ~ Max. | | | | Opposite Size | Small Screw | Diameter | | Height | | kg | lbs. |
| | S.I. | Metric | American | | | | mm | mm | in | mm | | |
| TP2.5N | N.m 0.25-2.5 | kgf.cm 2.5-25 | in.lbs 2-22 | TCF02N - TCF4N | 8 | M4 | 18 | 23/32 | 58 | 2 5/8 | 0.08 | 5/32 |
| TP18N | 1.8-18 | 18-180 | 16-160 | TCF10N, TCF20N | 13 | M6 | 35 | 1 3/8 | 83.5 | 3 7/16 | 0.27 | 21/32 |
| TP180N | 18-180 | 180-1800 | ft.lbs 30-130 | TCF100N, TCF200N | 24 | | 65 | 2 9/16 | 148 | 5 13/16 | 1.9 | 4 5/8 |
| TP1800N | 180-1800 | 1800-18000 | 130-1300 | TCF1000N, TCF2000N | 50 | | 140 | 5 1/2 | 297.5 | 11 23/32 | 16.8 | 36 1/8 |

| Model | Adapting Model | Chuck Grip | | Dimension | | | |
|--------|----------------|------------|---------|-----------|-----------|--------|-----------|
| | | mm | in | Diameter | | Height | |
| DTF5-3 | TCF02N-TCF4N | Max 5 | Max 1/8 | 33 mm | 1 5/16 in | 65 mm | 2 9/16 in |
| DTF5-2 | TCF10N-TCF40N | | | | | 61 mm | 2 3/8 in |

| Model | Attachment | Adapting Model | Chuck Grip | | Diameter | |
|-------|------------|----------------|------------|----------------|----------|---------|
| | | | mm | in | mm | in |
| TTF7 | ATF18-2 | TCF02N ~ TCF4N | Ø10 ~ 70 | 13/32 ~ 2 3/4 | 70 | 2 3/4 |
| TTF11 | ATF180 | TCF10N, TCF20N | Ø14 ~ 110 | 9/16 ~ 4 11/32 | 110 | 4 11/32 |
| TTF19 | ATF18-2 | TCF2N-TCF4N | Ø18 ~ 190 | 23/32-7 15/32 | 180 | 7 3/32 |
| | ATF180 | TCF10N-TCF20N | | | | |

NOTE

ATF attachment is required to fix TTF table to TCF model.


[Print](#)

[Close](#)

