

FR



Beam type torque wrenches for high torque range.



Select proper model according to unit of measure as following color code :

S.I. = Metric = American =

Accuracy ±3%

Model			Torque Range						Hand force at Max. Torque		Effective Lgth.		Overall Lgth.		Square Drive		Weight approx.	
			Min.-Max.			graduation												
S.I.	METRIC	AMERICAN	S.I.	METRIC	AMERICAN	S.I.	METRIC	AMERICAN	N	lb.	mm	in.	mm	in.	mm	in.	kg	lb.
FR1050N	10500 FR	10500 FR-A	100-1050	10-105	100-750	20	2	20	1340	286 55/64	797	31 3/8	835	32 7/8	25.4	1	8	17 21/32
FR1400N	14000 FR	14000 FR-A	200-1400	20-140	100-1000			20	1510	324 5/16	940	37	981	38 5/8			11.5	25 1/4
FR2100N	21000 FR	21000 FR-A	300-2100	30-210	200-1500	50	5	50	1940	415 37/64	1100	43 5/16	1148	45 3/16	38.1	1 1/2	14.5	32
FR2800N	28000 FR	28000 FR-A	300-2800	30-280	200-2000			50	2320	491 43/64	1240	48 13/16	1292	50 7/8			20	44
FR4200N	42000 FR	42000 FR-A	400-4200	40-420	300-3000	100	10	50	3050	653 7/16	1400	55 3/32	1460	57 15/32	28	61 3/4		
FR6000N	60000 FR	60000 FR-A	600-6000	60-600	400-4300			50	3960	848 15/16	1540	60 25/32	1624	63 15/16	30	66 5/32		

NOTE

FR models are supplied upon request.



Print



Close