


CDB-S



Interchangeable head and dial indicating type torque wrench.



Select proper model according to unit of measure as following color code :

S.I. = Metric = American =

Accuracy $\pm 3\%$

Model			Torque Range						Hand Force at Max Torque Range		Effective Lgth.		Overall Lgth.		Weight approx.		Interchangeable Heads
			Min.-Max.			Graduation											
S.I.	Metric	American	S.I.	Metric	American	S.I.	Metric	American	N	lb.	mm	in.	mm	in.	lb.	kg	
CDB7N X 8D-S	70CDB-S	70CDB-A-S	N.m 0.7-7	kgf.cm 7-70	in.lbs 6-60	0.1	1	1	30.4	6 49/64	230	8 55/64	232	8 15/16	59/64	0.42	(SH,RH,QH,HH) 8D
CDB14N X 8D-S	140CDB-S	140CDB-A-S	2-14	20-140	20-120	0.2	2	2	60.9	13 35/64							
CDB25N X 10D-S	250CDB-S	250CDB-A-S	3-25	30-250	25-220	0.5	5	5	96.2	21 31/64	260	10 15/64	255	10 3/64	1 1/16	0.48	(SH,RH,QH,HH, DH) 10D
CDB50N X 12D-S	500CDB-S	500CDB-A-S	5-50	50-250	40-430				161.3	35 13/64	310	12 13/64	329.5	12 31/32	1 11/64	0.53	(SH,RH,QH,RQH, HH,DH) 12D
CDB100N X 15D-S	1000CDB-S	1000CDB-A-S	10-100	100-1000	ft.lbs 7-70	1	10	1	256.4	54 43/64	390	15 23/64	412.5	16 15/64	1 43/64	0.76	(SH,RH,QH,RQH, HH,DH) 15D
CDB200N X 19D-S	2000CDB-S	2000CDB-A-S	20-200	200-2000	14-140	2	20	2	388.3	83 43/64	515	20 5/64	524.5	20 29/64	2 13/64	1	(SH,RH,QH,RQH, HH,DH) 19D
CDB300N X 22D-S	3000CDB-S	3000CDB-A-S	30-300	kgf.m 3-30	20-220	5	kgf.m 0.5	5	413.8	92 15/32	725	28 35/64	717.5	28 1/4	3 41/64	1.65	(SH,RH,QH,RQH, HH,DH) 22D
CDB420N X 22D-S	4200CDB-S	4200CDB-A-S	40-420	4-42	30-300				454.1	98 27/32	925	36 27/64	918	36 9/64	5 61/64	2.7	

NOTE

- Overall length does not include interchangeable head.
- PH type interchangeable head is not available for this model.



Print



Close